

Products and Specifications



	MovinCool®						Big Ass Fans	OceanAire	Kwikool 12 ton units		Indirect Fired Heaters	
	Office Pro 36"	Office Pro 60"	Office Pro 63"	Classic Plus 14	Classic Plus 26	Classic 60	Black Jack	20ACH (1811)	KPO 12-43	KPO 12-23	FVO-400	FVPN-400
Dimensions	30" x 40" x 52"	30" x 52" x 64"	30" x 52" x 64"	19" x 26" x 41"	19" x 29" x 47"	32" x 49" x 42"	84" x 78" x 29"	40.5" x 24" x 30" (w/o casters)	36" x 64" x 52" (w/o 8" wheels)	32" x 64" x 52" (w/o 8" wheels)	70" x 29" x 52"	70" x 29" x 47"
Capacity (95° F at 60% RH)	36,000 BTU	60,000 BTU	60,000 BTU	13,200 BTU	24,000 BTU	60,000 BTU		16,800 BTU	135,000 BTU	135,000 BTU	390,000 BTU	390,000 BTU
Control Features	Programmable	Programmable	Programmable	Programmable	Programmable	Digital	Variable speed control	Heat Pump/AC	Digital thermostat	Digital thermostat	Direct spark ignition	Direct spark ignition
<i>Voltage Requirement</i>	1 Phase, 208/230V	1 Phase, 208/230V	3 Phase, 460V	1 Phase, 115V	1 Phase, 208/230V	3 Phase, 460V	110V	115 V, 60 Hz, Single Phase	3 Phase, 460V	3 Phase, 208-230V	115V/60Hz/1Ph/ 20Amp	115V/60Hz/1Ph/ 20Amp
<i>Total Power Consumption</i>	4.3 kW	6.6 kW	6.6 kW	1.3 kW	2.4 kW	5.9 kW					2.81 Gallons per hour (14 hour life)	Propane - 4.26 GPH Natural Gas - 390 CFH
<i>Current Consumption</i>	19.6 amps	29 amps	9.5 amps	11.9 amps	10.8 amps	8.8 amps	7.5 amps	14.1 amps	36 amps	72 amps		
<i>Recommended Fuse Size</i>	30 amps	50 amps	20 amps	15 amps	20 amps	20 amps	20 amps	Time delay fuses/ circuit breakers recommended	40/50 amps	80 amps		
<i>NEMA Plug Configuration</i>	6-30	6-50	L16-20	5-15	6-20	N/A		14/3 5-20P, LCDI	Color Coded Cam Locks	Color Coded Cam Locks		
<i>Min-Max Voltage</i>	198 - 250	198 - 250	440 - 480	105 - 125	198 - 250	440 - 480	max 471 Watts	115 Volts	420 - 500	195-225/210-250		